

ULTRABOND TURF TAPE 300

Seaming tape for synthetic installation

DESCRIPTION

Ultrabond Turf Tape 300 is a spun-bonded, coated non-woven polyester fabric, specifically designed for seaming artificial turf. **Ultrabond Turf Tape 300** is waterproof and provides both superior tensile strength and tear resistance, which is of paramount importance for installations of professional sport fields. It is also perfectly suited as a seaming tape for other artificial turf applications, including installations of residential landscaping, playgrounds and golf courses.

FEATURES AND ADVANTAGES

- Superior tensile and shear strength.
- Meets FIFA Quality Programme protocol.

WHERE TO USE

- Interior and exterior synthetic grass installations.
- Professional and educational sports field arenas.
- Commercial and residential landscaping applications of synthetic turf.

PACKAGING

Ultrabond Turf Tape 300 is supplied in 300 m rolls.

STORAGE AND WASTE DISPOSAL

Ultrabond Turf Tape 300 is stable in ordinary working conditions. It is advised to store the product at the site in its original sealed packaging. According to current local regulations regarding waste disposal, the product may be disposed of in an authorized waste tip, a recycling plant for plastics or an authorized thermo-reducing plant.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATIONS

Ultrabond Turf Tape 300 is an article and referring to the current European regulations (Reg. 1906/2007/CE - REACH) does not require the preparation of the material safety data sheet. During use it is recommended to wear gloves and goggles and follow the safety requirements of the workplace.

For further and complete information about the safe use of our product please refer to the latest version of our Material Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

TECHNICAL DATA (typical values)	
PRODUCT IDENTITY	
Fabric type:	spun-bonded polyester
Colour:	white
Thickness (EN ISO 9073-2) (mm):	0,5 ± 5%
Standard roll strength (EN 1848-2) (m):	300
Width (En 1848-2) (m):	0,3
Mass per unit area (EN 1849-2)(g/m ²):	175 ± 10%
Tensile strength at break (longitudinal, EN 12311) (N/50 mm):	410 ± 15%
Tensile strength at break (transversal, EN 12311) (N/50 mm):	360 ± 15%
Elongation at break (longitudinal, EN 12311) (%):	34 ± 10%
Elongation at break (transversal, EN 12311) (%):	37 ± 10%
Shelf life:	unlimited

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

591-4-2018-gb

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

