



NEW

# Mapecfloor Wax Remover

**Special multi-action,  
de-waxing detergent  
for Mapelux cross bond,  
metallic wax**



## WHERE TO USE

**Mapecfloor Wax Remover** is used in environments for civil use, such as shops, showrooms, apartments, offices etc., to remove surface films of old metallic wax from floors treated with **Mapelux**.

**Mapecfloor Wax Remover** has been specially developed to remove metallic wax, especially **Mapelux Lucida** and **Mapelux Opaca** cross bond metallic waxes.

It may also be used for deep-down cleaning and for removing wax from linoleum and/or rubber floors (in the case of old floors with this type of material, test beforehand to check for colour-fastness).

## Some application examples

- De-waxing treatment for **Mapelux** protective films on resin floors made using the **Mapecfloor System** and/or the **Ultratop System**, including those mixed with **Dynastone Color** or natural aggregates, in environments for civil use before re-waxing the floor.

## TECHNICAL CHARACTERISTICS

**Mapecfloor Wax Remover** is a multi-action, low-foaming wax-removal detergent for deep-down cleaning and removal of all types of metallic wax.

It is particularly suitable for removing old films of cross bond metallic wax, such as **Mapelux Lucida/Mapelux Opaca**.

Its deep-cleansing action attacks all the components in

the wax film, and quickly emulsifies residual materials and dirt.

The product contains a minimum of 90% of primary bio-degradable surfactant components and complete aerobic biodegradation, which conforms to Reg. (CE) N° 648/2004.

## How to use

For normal metallic waxes, use at a concentration of from 5 to 10% (0.5-1 l in 10 l of water).

For cross bond metallic waxes such as **Mapelux**, use at a concentration of 15% (1.5 l in 10 l of water). Use a white cleaning disk, vacuum the surface and then rinse.

## PACKAGING

**Mapecfloor Wax Remover** is available in 10 kg cans.

## STORAGE

**Mapecfloor Wax Remover** can be stored for 12 months in its original packaging at a temperature between +10°C and +30°C. Protect from frost.

## SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

**Mapecfloor Wax Remover** is corrosive, and may cause burns if it comes into contact with the skin. We recommend the use of protective gloves and goggles when using the product, and to rinse off thoroughly with plenty of water if it comes into contact with the skin.

# Mapefloor Wax Remover



TECHNICAL DATA (typical values)	
<b>PRODUCT IDENTITY</b>	
<b>Appearance:</b>	liquid
<b>Colour:</b>	pink
<b>Density (g/cm<sup>3</sup>):</b>	1.009
<b>Content of active substances (%):</b>	44
<b>pH of concentrated product:</b>	11.7 ± 0.2
<b>Ross Miles depth of foam (ASTM D.459/47):</b>	0 after 3 minutes
<b>Solubility in water:</b>	soluble
<b>Solubility in oil:</b>	insoluble
<b>Storage:</b>	12 months in its original, well-sealed packaging
<b>Hazard classification according to EC 1999/45:</b>	corrosive. Before using refer to the "Safety instructions for preparation and application" paragraph and the information on the packaging and Safety Data Sheet
<b>Customs class:</b>	3814 00 90

For further information, please refer to the Safety Data Sheet.

FOR PROFESSIONAL USERS.

### WARNING

*While the indications and guidelines contained in this data sheet correspond to the company's knowledge and wide experience, they must be considered, under all circumstances, merely as an indication and subject to confirmation only after long-term, practical applications. Therefore, anybody*

*who undertakes to use this product, must ensure beforehand that it is suitable for the intended application and, in all cases, the user is to be held responsible for any consequences deriving from its use.*

**All relevant references  
for the product are available  
upon request and from  
[www.mapei.com](http://www.mapei.com)**