

POROMAP RINZAFFO PLUS Declaration of Performance N. CPR-IT1/0730

DECLARATION OF PERFORMANCE N. CPR-IT1/0730

- 1) Unique identification code of the product-type: POROMAP RINZAFFO PLUS
- 2) Intended uses: Designed general purpose rendering/plastering mortar (GP) for external and internal use on walls, ceilings, columns and partitions
- 3) Manufacturer: MAPEI S.p.A. Via Cafiero, 22 20158 Milan Italy www.mapei.it

4) Systems of AVCP: System 4

5) Harmonized standards: EN 998-1:2016

Notified bodies: No task for the notified body

6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	Class A1
Water absorption:	W _c 1
Water vapour permeability:	μ ≤ 20
Adhesion:	≥ 0,5 N/mm ² – FP:B
Thermal conductivity:	0,57 W/m·K (tab. mean value λ _{10,dry,mat} ; P=50%)
Durability:	NPD
Dangerous substances:	NPD

7) Appropriate Technical Documentation: included, as long as needed, in the technical dossier stored by the manufacturer. Reaction to fire class declared without the need for testing according to the Decision of the Commission 96/603/EC and following amendments. Organic material <1% by mass and volume.</p>

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) no. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Lorenzo Martino - Corporate Quality Management

Milan, 26/07/2022

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the Safety Data Sheet that MAPEI makes available on the website along with this current Declaration of Performance.

DoP in Pdf format are available in the Mapei website.

Revision 1 notes: Product unchanged, updated DoP layout

POROMAP RINZAFFO PLUS CE MARKING

Annex to DoP N. CPR-IT1/0730







Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it

19

CPR-IT1/0730 EN 998-1

POROMAP RINZAFFO PLUS

Designed general purpose rendering/plastering mortar (GP) for external and internal use on walls, ceilings, columns and partitions

Reaction to fire: Class A1 Water absorption: W_C 1 Water vapour permeability: $\mu \le 20$

Adhesion: $\geq 0.5 \text{ N/mm}^2 - \text{FP:B}$

Thermal conductivity: 0,57 W/m·K (tab. mean value $\lambda_{10,dry,mat}$; P=50%)

Durability: NPD
Dangerous substances: NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the CE marking,
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.